

IN ADDITION TO MARKINGS OF THE SPECIFICATION,  
 SCREW SHALL HAVE AN ALPHA CODE IN  
 ACCORDANCE WITH TABLE I MARKED TWICE ON THE  
 SIDE OF THE HEAD, 180 DEGREES APART. ALPHA  
 CODE SHALL BE 0.125 LETTERS, STAMPED 0.005  
 TO 0.030 DEEP.

TABLE I

{CODE}	{LENGTH}	{SIZE}
A	0.875	0.312
B	1.000	0.312
C	1.250	0.312
BE	1.500	0.312
D	1.750	0.312
E	2.000	0.312
F	2.125	0.312
BD	2.250	0.312
G	0.875	0.375
H	1.000	0.375
J	1.250	0.375
K	1.750	0.375
L	2.000	0.375
M	2.125	0.375
N	2.250	0.375
P	2.500	0.375
R	2.625	0.375
S	1.250	0.438
AX	1.375	0.438
T	1.500	0.438
U	1.750	0.438
V	2.000	0.438
W	2.250	0.438
AY	2.375	0.438
X	2.500	0.438
BH	2.650	0.438
Y	2.750	0.438
Z	2.875	0.438
AA	3.000	0.438
AB	3.250	0.438
AC	3.500	0.438
BJ	4.000	0.438
AD	1.750	0.500
AE	2.000	0.500
AF	2.250	0.500
AG	2.500	0.500

AH	2.750	0.500
AJ	3.000	0.500
AK	3.250	0.500
AL	3.500	0.500
AM	3.750	0.500
AN	4.000	0.500
AP	4.250	0.500
BG	1.750	0.625
BL	2.000	0.625
AR	2.250	0.625
AS	2.500	0.625
AT	2.750	0.625
BM	3.250	0.625
AU	4.500	0.625
AV	4.750	0.625
AW	5.000	0.625
BK	5.250	0.625
BN	2.750	0.750
BC	3.125	0.750
AZ	3.500	0.750
BA	4.750	0.750
BB	5.250	0.750
BF	5.500	0.750