

Coded Note Number: IC040

Revision: C002

Date: May 30, 2017

Title: Packing and Shipping Requirements

This revision history is provided for convenience and does not alleviate the supplier's responsibility with understanding and complying with the full coded note.

Bolded font indicates changed/added content.

[text *deleted*] inserted in the document indicates the removal of content.

Packing and shipment shall be such that material is not damaged and that tags on each item shall remain intact, in place and legible for short time storage and handling after receipt. Packing shall ensure maintenance of the degree of cleanliness required for the component or part until delivered and accepted at the shipping destination.

The use of yellow wrapping or yellow protection devices such as caps and plugs are strictly prohibited.

Each shipping container shall be substantially marked with the item and purchase order numbers.

All machined surfaces such as flange faces (phonographic finish), end preps, threads (male/female), etc. shall be protected from potential damage from material transport/storage using caps/covers/plugs made of silicon rubber, stainless steel, aluminum, rigid Teflon, rigid polyethylene, ethylene propylene rubber, nitrile butadiene (Buna-N) rubber, polyamide (Nylon), acetal homopolymer (Delrin), or rigid polyurethane (Pellethane). Clear materials are not allowed. Sealing tape must be 3M Performance Plus Duct Tape 8979N, slate blue in color.