

Coded Note Number: **IC197**

Revision: **C009**

Dated: **April 29, 2013**

Title: **Tagging of Hose/Hose Assemblies for Safe Handling Instructions**

A metal tag with **Type II Electrochemical Etched; Type V Die Stamped; or Type VIII Laser Engraved**, (round bottom) 1/8 inch (minimum) characters per MIL-STD-792, shall be attached to each end of the Hose/Hose Assembly. The tags must be attached with a wire in such a way as to not interfere with end connection containments. The vendor shall insert the appropriate information in each blank below. The tags shall contain the following information:

\*\*\*\*\* SPECIAL HANDLING INSTRUCTIONS FOR HOSE \*\*\*\*\*

DO NOT EXCEED MINIMUM BEND RADIUS OF \_\_\_\_\_

DO NOT TWIST OR TORQUE. DO NOT BEND HOSE AT END FITTINGS.

COILED HOSES MUST BE UPRIGHTED AND UNROLLED THROUGH ITS FULL LENGTH.

DATE OF MANUFACTURE \_\_\_\_\_

VENDOR HYDRO TEST PRESSURE \_\_\_\_\_ PSI & DATE \_\_\_\_\_

MAXIMUM WORKING PRESSURE \_\_\_\_\_ PSI