

## T1710-19960324

THE PREFERRED IDENTIFICATION METHOD FOR SPOOLED WELDING WIRE IS LABELS PLACED ON SPOOLS AND AS A MINIMUM MUST COMPLY WITH THE FOLLOWING:

APPLIED WITH A STRONG ADHESIVE.

PRINTED ON DURABLE MATERIAL THAT WILL REMAIN INTACT UNTIL WIRE IS CONSUMED.

PLACED ON SPOOL FLANGE TO AVOID COVERING SPINDLE HOLE OR OTHER VOIDS IN SPOOL SURFACE.

PRINTED SO THAT THE MIL-TYPE AND WIRE DIAMETER SIZE IS IN LARGE/BOLD LETTERS (3/16" HIGH MINIMUM).

AS AN ALTERNATE MARKING METHOD, STENCILLING WILL BE ACCEPTED AT NNS PROVIDED THE STENCILLING MEETS THE FOLLOWING CRITERIA.

1. APPLIED WITH DURABLE MATERIAL THAT WILL NOT FADE, RUN OR RUB OFF.
2. IS ARRANGED ON THE SPOOL FLANGE SO THAT ALL CHARACTERS ARE READABLE AND NOT MISSING DUE TO THE SPINDLE HOLE OR OTHER VOIDS.
3. LETTERING MEETS THE SAME CRITERIA FOR SIZE AS DESCRIBED ABOVE.